



Unique flow arrangement enables Inlet & Outlet flow to be inline without any change of flow direction.

Models		Dimensions											Weight kg	Volume Per Side Litres
Copper Brazed	Stainless Brazed	A mm	B mm	C mm	D mm	E mm	F mm	G BSP	H mm	K mm	L mm	M mm		
10-5	-	106	50	-	-	25	-	1/2"	11	24	16	3	0.8	0.05
10-9	10-9E	106	50	-	-	25	-	1/2"	11	37	16	3	0.9	0.11
10-13	-	106	50	-	-	25	-	1/2"	11	50	16	3	1.1	0.16
10-17	10-17E	106	50	-	-	25	-	1/2"	11	63	16	3	1.2	0.21
10-21	-	106	50	-	-	25	-	1/2"	11	76	16	3	1.3	0.26
10-25	-	106	50	-	-	25	-	1/2"	11	90	16	3	1.7	0.32
10-29	-	106	50	-	-	25	-	1/2"	11	103	16	3	2.0	0.37
<b>Separator</b>														
15-5	-	158	75	165	7	37.5	45	3/4"	12	34	20	4	2.5	0.18
15-9	15-9E	158	75	165	7	37.5	45	3/4"	12	54	20	4	2.9	0.36
15-13	15-13E	158	75	165	7	37.5	45	3/4"	12	74	20	4	3.3	0.55
15-17	-	158	75	165	7	37.5	45	3/4"	12	94	20	4	3.7	0.72
15-21	-	158	75	165	7	37.5	45	3/4"	12	112	20	4	4.1	0.90
15-25	15-25E	158	75	165	7	37.5	45	3/4"	12	132	20	4	4.6	1.09
15-29	-	158	75	165	7	37.5	45	3/4"	12	152	20	4	5.0	1.27
<b>Separator</b>														
20-5	-	215	100	220	7	50	60	1"	12	45	24	5	5.4	0.44
20-9	-	215	100	220	7	50	60	1"	12	71	24	5	6.1	0.88
20-13	-	215	100	220	7	50	60	1"	12	97	24	5	6.8	1.32
20-17	20-17E	215	100	220	7	50	60	1"	12	123	24	5	7.6	1.76
20-21	-	215	100	220	7	50	60	1"	12	149	24	5	8.4	2.20
20-25	-	215	100	220	7	50	60	1"	12	175	24	5	9.2	2.64
20-29	20-29E	215	100	220	7	50	60	1"	12	201	24	5	10.2	3.08
<b>Separator</b>														
25-29	-	265	125	275	9	62.5	75	1 1/4"	15	249	28	6	18.8	6.02

Maximum working pressure 6 bar

Maximum working temperature 185°C

■ These products have been designed to operate with ethanol based fuels

**EJ Bowman (Birmingham) Ltd**

Chester Street, Birmingham B6 4AP, UK

Tel: +44 (0) 121 359 5401 Fax: +44 (0) 121 359 7495

Email: info@ejbowman.co.uk www.ejbowman.co.uk



BS EN ISO 9001-2008  
Reg. No. FM38224



A World Leader in Heat Exchanger Technology